

THE REAL IN LINE BRIX/CO₂ analyzer for beverages

The beverage analyzer IB07 is the only 100% in line system able to measure accurately Bx and CO₂ of any regular carbonated beverage including fruit juice with fibers, energy drinks and mineral waters.

The equipment is based on optical technology: refractive index for Bx measurement and infrared for CO₂ one.

Both analyzers do not have any drift in the time so that the Maselli IB07 acts like a “black box” which does not need any adjustment vs the laboratory: after the initial configuration during start up, the operators in the plant do not have to touch the system anymore.

The Maselli IB07 may be delivered in 3 different configurations: only Bx, only CO₂ or the combination Bx/CO₂ but, in any case, the installation can be easily made by means of 1 single Varivent fitting.

Due to the optical technology, the equipment is virtually no maintenance reducing drastically the ownership costs.



IB07

BEVERAGE ANALYZER

BRIX AND CO₂ FOR THE BEVERAGE INDUSTRY

Field Control Panel

MP06 Receiver

MP06 is the new control panel for Maselli in line beverage analyzers: robust IP67 construction in a quick installation and implementation package.

By means of a touch screen panel, the operator may navigate through the intuitive software in order to monitor the trends, to handle the alarms and to make decisions about process control.

The innovative MP06 design is based on web server philosophy so that either using the ethernet network of the plant or simply a smartphone as hot spot, it is possible to enable a remote connection useful for trouble shooting or training



MP06

OPERATING SPECIFICATION

Concentration Measurement

Measurement range:	0...20 Brix
Accuracy:	±0.02 Brix
Measurement scale:	BRIX
Response time:	1 second

CO₂ Measurement

Measurement range:	0...6 v/v (0...12 g/l)
Reproducibility:	+/- 0.025 v/v (+/- 0.05 g/l)
Measurement scales:	"v/v (Gas/Vol)" or "g/l"
Measurement interval:	1.8 sec

TECHNICAL FEATURES

Product Temperature:	-5...+35 °C [23...95 °F]
Line pressure:	max 10 bar (145 psi) at 20 °C (68 °F) max 8 bar (116 psi) at 105 °C (221 °F) Special version for pressures up to 15 bar (217 psi) at 100 °C (212 °F)
Degree of protection:	IP67 to EN60529
Power supply:	AC 100V...240V ±10% 50...60Hz, 150VA. DC 24V ±10%, 10A Max.
Digital interface:	RS485 for connection to M8, MP06 receivers Profibus DP, MODBUS/TCP, ETHERNET/IP, PROFINET
Line connection:	Tuchenhagen Varivent N

Please refer to the technical datasheet for further data.

More products for the Beverage Industry

IB08

Beverage Analyzer



In Line - Bx/Diet/CO₂

LP10

Laboratory Soft drink
Analyzer



Laboratory – Diet, Brix,
Fresh Brix, CO₂



maselli
PROCESS ANALYZERS

43122 Parma - Italy - Tel. +39.0521.257411
www.maselli.com

